



DESERT: Split on/off



Series	DESERT: Split on/off
Model	SPLTONOF-24
QCC Registration	Performace
Capacity	2 Ton
Indoor Model	MSTAG11D-23CRN1-QC5
Outdoor Model	MOTX430-23CN1-QC5
Region	UAE


Features

 Turbo Mode-60% Fast Cooling

 Golden Fin-50-year corrosion resistance

 3D Air Flow-4-way swing

 Super Silent-Optimised design for low noise

 Hidden LED-Night display

DESERT: Split on/off

Power Supply	220-240V 50Hz, 1Ph(V~,Hz,Ph)
--------------	------------------------------

Cooling (T1)

Capacity	23200 (Btu/h)
Input	1940 (W)
Rated current	8,55 (A)
EER	11,959 (Btu/h/W)

Cooling (T3)

Capacity	20000 (Btu/h)
Input	2320 (W)
Rated current	10,23 (A)
EER	8,621 (Btu/h/W)

Max. input consumption	2900 (W)
Max. current	19 (A)
Starting current	48 (A)

Indoor Fan Motor

Model	ZKFP-58-8-1-5
Input	116 (W)
Output	58 (W)
Capacitor	/ (uF)
Speed(Turbo/Hi/Mi/Lo)	1450/1200/1120/1050 (r/min)

Compressor

Model	ASG240VISFT
Type	ROTARY
Brand	GMCC
Capacity	20557 (Btu/h)
Input	1930 (W)
Rated current(RLA)	8,3 (A)
Locked rotor Amp(LRA)	48 (A)
Thermal protector	/
Thermal protector position	INTERNAL
Capacitor	55 (uF)
Refrigerant oil/oil charge	VG75/610 (ml)

Indoor Coil

Number Of Row	2
Tube Pitch(a)x Row Pitch(b)	21x13.37 (mm)
Fin spacing	1.3 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	820x336x26.74 (mm)
Number of circuits	4

Indoor air flow (Turbo/Hi/Mi/Lo)	1400/1150/1050/1000 (m3/h)
Indoor noise level (Turbo/Hi/Mi/Lo)	52/47/45/43 (dB(A))

DESERT: Split on/off

Indoor unit

Dimension(W*D*H	1082x234x337 (mm)
Packing (W*D*H)	1155x415x315 (mm)
Net/Gross weight	13.8/17.4 (Kg)

Outdoor fan motor

Model	YKT-65-6-240L
Input	135 (W)
Output	65 (W)
Capacitor	5 (uF)
Speed(Turbo/Hi/Mi/Lo)	825 (r/min)

Outdoor coil

Number Of Row	2.6
Tube Pitch(a)x Row Pitch(b)	21x13.37 (mm)
Fin spacing	1.3 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	910x609x26.74+540x609x13.37 (mm)
Number of circuits	6

Outdoor unit

Dimension(W*D*H)	890x342x673 (mm)
Packing (W*D*H)	995x398x740 (mm)
Net/Gross weight	50.4/53.6 (Kg)

Outdoor noise level (dB(A))	60 (dB(A))
Refrigerant type	R410A/1750g (g)
Design pressure	4.8/1.5 (MPa)

Refrigerant piping

Liquid side/ Gas side	Φ9.52/Φ15.9(3/8"/5/8" (mm(inch))
Max. refrigerant pipe length	25 (m)
Max. difference in level	10 (m)

Connection wiring	2.5x4
Plug type	2.5x3/no-plug
Thermostat type	Remote Control
Operation temperature	17~30 (°C)

Room temperature

Indoor(cooling/ heating)	17-32/---- (°C)
Outdoor(cooling/heating)	18~52/--- (°C)

Application area(Cooling Standard)	31-46(m2)
------------------------------------	-----------