

Cassette 4 way unit



Series	Cassette 4 way unit
Model	WSGV-1000-VS-4NS
QCC Registration	QCC Registration
Capacity	1000CFM 2,5TON 9KW
Region	UAE

Features

Return AIR Plenum and Fllter Air Standard

Adjustable ESP

External Static Pressure

Cassette 4 way unit

Power Supply	220~240V,50Hz,1 (V~,Hz,Ph)
Cooling Capacity	9018/7665/5862 (w)
Heating Capacity	13512/11485/8783 (w)

Indoor Fan Motor

Type	Low noise 3-speed fan motor (XD80A)
Number of motor	1
Output Power	165 (W)
Capacitor	6.0 (uF)

Indoor Fan

Number of Fan	1
Type	Centrifugal wind wheel (White material)

Water Flow Volume	1,68 (m3/h)
Hydraulic Resistance	36 (Kpa)
Max.Working pressure	1,6 (Mpa)

Weight

Panel Net/Gross	5/7 (kg)
Body Net/Gross	26.5/31 (kg)

Wiring specification

Power Wiring (FCU)	3×1 (mm2)
--------------------	-----------

Air Flow Volume (H/M/L Speed)	
1000/750/500 (CFM)	1700/1275/850 (m3/h)

Indoor Coil

Number Of Row	2
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,5 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
f.Coil Length x Height x Width	2044*246*25.4 (mm)

Dimension

Net Dimension (body)	835×835×290 (mm)
Packing Dimension(body)	910×910×310 (mm)
Net Dimension (Panel)	950×950×55 (mm)
Packing Dimension (Panel)	1000×1000×100 (mm)

Noise Level	≤48 (dB(A))
Drain Pipe	DN20 (mm)
Inlet/Outlet Water Pipe	DN20 (mm)