

Cassette 4 way unit



Series	Cassette 4 way unit
Model	WSGV-300-VS-4NS
QCC Registration	QCC Registration
Capacity	300CFM 0,9TON 3,3KW
Region	UAE

Features

Return AIR Plenum and Filter Air Standard

Adjustable ESP

External Static Pressure

Cassette 4 way unit

Power Supply	220~240V,50Hz,1 (V~,Hz,Ph)
Cooling Capacity	3300/2840/2380 (w)
Heating Capacity	4800/4200/3700 (w)

Indoor Fan Motor

Type	Low noise 3-speed fan motor (XD30B)
Number of motor	1
Output Power	55 (W)
Capacitor	1.5 (uF)

Indoor Fan

Number of Fan	1
Type	Centrifugal wind wheel (White material)

Water Flow Volume	0,62 (m3/h)
Hydraulic Resistance	26 (Kpa)
Max.Working pressure	1,6 (Mpa)

Weight

Panel Net/Gross	3/5 (kg)
Body Net/Gross	18/20.3 (kg)

Wiring specification

Power Wiring (FCU)	3×1 (mm2)
--------------------	-----------

Air Flow Volume (H/M/L Speed)	
300/259/212 (CFM)	510/440/360 (m3/h)

Indoor Coil

Number Of Row	2
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,5 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
f.Coil Length x Height x Width	1322*205*25.4 (mm)

Dimension

Net Dimension (body)	570×570×260 (mm)
Packing Dimension(body)	650×650×290 (mm)
Net Dimension (Panel)	650×650×55 (mm)
Packing Dimension (Panel)	710×710×80 (mm)

Noise Level	≤39 (dB(A))
Drain Pipe	DN20 (mm)
Inlet/Outlet Water Pipe	DN20 (mm)