

Wall-mounted indoor unit





|                  |                          |
|------------------|--------------------------|
| Series           | Wall-mounted indoor unit |
| Model            | WSTBEZ-J036-MT1F(K)      |
| QCC Registration | QCC Registration         |
| Capacity         | 1 TON / 3.6 KHW          |
| Region           | UAE                      |

Features

Superb Craftsmanship

Wired Control

2 Ways Draining Connection

Wall-mounted indoor unit

|                  |                             |
|------------------|-----------------------------|
| Power Supply     | 220~240,50(60),1 (V~,Hz,Ph) |
| Cooling Capacity | 3,6 (kW)                    |
| Heating Capacity | 4,0 (kW)                    |

Indoor Fan Motor

|              |                       |
|--------------|-----------------------|
| Model        | D-310-13-8C 310V      |
| Brand        | WEILING               |
| Output Power | 20 (W)                |
| Capacitor    | / (uF)                |
| Speed        | 1100/1000/900 (r/min) |

Indoor Coil

|                               |                           |
|-------------------------------|---------------------------|
| Number Of Row                 | 2                         |
| Tube Pitch(a)x Row Pitch(b)   | 20.5×12.7 (mm)            |
| Fin Pitch                     | 1,4 (mm)                  |
| Fin Material                  | Hydrophilic aluminum fin  |
| Tube Outside Dia.And Material | φ7， Inner grooved (mm)    |
| Coil Length x Height x Width  | 652*184*25.4 522*103*25.4 |
| Heat Exchanging Area          | 5,16 (m2)                 |

Indoor Unit

|                               |                    |
|-------------------------------|--------------------|
| Indoor Air Flow (Tu/Hi/Mi/Lo) | 520/460/400 (m3/h) |
| Noise Level(Tu/Hi/Mi/Lo)      | 38/33/27 (dB/A)    |
| Net Dimension (W×D×H)         | 881x294x194 (mm)   |
| Packing Dimension (W×D×H)     | 965×370×282 (mm)   |
| Net Weight                    | 10,5 (kg)          |
| Gross Weight                  | 13 (kg)            |
| Extemal Static Pressure       | 0 (Pa)             |

Refrigerant Pipe

|             |                   |
|-------------|-------------------|
| Liquid Side | 6.35(1/4) (mm)    |
| Gas Side    | 9.52(3/8) (mm)    |
| Drainage    | R3/4in(DN20) (mm) |

Wiring specification

|                                     |                    |
|-------------------------------------|--------------------|
| Power Wiring (Indoor)               | 3×1.5 (mm)         |
| A B Signal Wiring(IDU&ODU, IDU&IDU) | 2×0.5 (mm)         |
| Stuffing Quantity (20/40/40H)       | 316/647/737 (Unit) |
| Operation Temperature Range         | 16~32 (°C)         |
| Application Area                    | 15~30 (m2)         |