

Wall-mounted indoor unit





Series	Wall-mounted indoor unit
Model	WSTBEZ-J056-MT1F(K)
QCC Registration	QCC Registration
Capacity	1.6 TON / 5.6 KWH
Region	UAE

Features

Superb Craftsmanship

Wired Control

2 Ways Draining Connection

Wall-mounted indoor unit

Power Supply	220~240,50(60),1 (V~,Hz,Ph)
Cooling Capacity	5,6 (kW)
Heating Capacity	6,3 (kW)

Indoor Fan Motor

Model	D-310-30-8 310V
Brand	WEILING
Output Power	30 (W)
Capacitor	/ (uF)
Speed	1100/1000/900 (r/min)

Indoor Coil

Number Of Row	2
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,4 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	723*205*25.4 572*123*25.4
Heat Exchanging Area	6,46 (m2)

Indoor Unit

Indoor Air Flow (Tu/Hi/Mi/Lo)	850/750/660 (m3/h)
Noise Level(Tu/Hi/Mi/Lo)	42/38/34 (dB/A)
Net Dimension (W×D×H)	997x316x227 (mm)
Packing Dimension (W×D×H)	1067x385x312 (mm)
Net Weight	13,5 (kg)
Gross Weight	16,5 (kg)
Extemal Static Pressure	0 (Pa)

Refrigerant Pipe

Liquid Side	6.35(1/4) (mm)
Gas Side	12.7(1/2) (mm)
Drainage	R3/4in(DN20) (mm)

Wiring specification

Power Wiring (Indoor)	3×1.5 (mm)
A B Signal Wiring(IDU&ODU, IDU&IDU)	2×0.5 (mm)
Stuffing Quantity (20/40/40H)	241/498/563 (Unit)
Operation Temperature Range	16~32 (°C)
Application Area	25~45 (m2)