

Floor & Ceiling



Series	Floor & Ceiling
Model	WSTBVG-J056-MT1FG
QCC Registration	QCC Registration
Capacity	1.6 TON / 5.6 KWH
Region	UAE

Features

Long Air Supply Distance

Beautiful Design of Display Board

Anti-condensation

Floor & Ceiling

Power Supply	220-240V,50/60,1 (V~,Hz,Ph)
Cooling Capacity	5,6 (kW)
Heating Capacity	6,3 (kW)

Indoor Fan Motor

Model	FP40D-ZL
Brand	WOLONG
Output Power	40 (W)
Capacitor	/ (uF)
Speed	1000/950/790/730/690 (r/min)

Indoor Coil

Number Of Row	3
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,5 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	691*307.5*38.1
Heat Exchanging Area	9,01 (m2)

Indoor Unit

Indoor Air Flow (Tu/Hi/Mi/Lo)	940/895/700/650/600 (m3/h)
Noise Level(Tu/Hi/Mi/Lo)	42/41/38/37/36 (dB/A)
Net Dimension (W×D×H)	1000×690×235 (mm)
Packing Dimension (W×D×H)	1080×770×325 (mm)
Net Weight	29 (kg)
Gross Weight	33,5 (kg)
Extemal Static Pressure	50(0-150) (Pa)

Refrigerant Pipe

Liquid Side	6.35(1/4) (mm)
Gas Side	12.7(1/2) (mm)
Drainage	R3/4in(DN20) (mm)

Wiring specification

Power Wiring (Indoor)	3×1.5 (mm)
A B Signal Wiring(IDU&ODU, IDU&IDU)	2×0.5 (mm)
Stuffing Quantity (20/40/40H)	112/224/264 (Unit)
Operation Temperature Range	16~32 (°C)
Application Area	25~45 (m2)