

Floor & Ceiling



Series	Floor & Ceiling
Model	WSTBVG-J112-MT1FG
QCC Registration	QCC Registration
Capacity	3.2 TON / 11.2 KWH
Region	UAE

Features

Long Air Supply Distance

Beautiful Design of Display Board

Anti-condensation

Floor & Ceiling

Power Supply	220-240V,50/60,1 (V~,Hz,Ph)
Cooling Capacity	11,2 (kW)
Heating Capacity	12,8 (kW)

Indoor Fan Motor

Model	FP120D-ZL
Brand	WOLONG
Output Power	120 (W)
Capacitor	/ (uF)
Speed	1300/1250/1080/960/900 (r/min)

Indoor Coil

Number Of Row	3
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,5 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	1291*307.5*38.1
Heat Exchanging Area	16,83 (m2)

Indoor Unit

Indoor Air Flow (Tu/Hi/Mi/Lo)	2040/1890/1740/1560/1440(m3/h)
Noise Level(Tu/Hi/Mi/Lo)	50/49/45/43/41 (dB/A)
Net Dimension (W×D×H)	1600×690×235 (mm)
Packing Dimension (W×D×H)	1680×770×325 (mm)
Net Weight	42 (kg)
Gross Weight	49 (kg)
Extemal Static Pressure	50(0-150) (Pa)

Refrigerant Pipe

Liquid Side	9.52(3/8) (mm)
Gas Side	15.88(5/8) (mm)
Drainage	R3/4in(DN20) (mm)

Wiring specification

Power Wiring (Indoor)	3×1.5 (mm)
A B Signal Wiring(IDU&ODU, IDU&IDU)	2×0.5 (mm)
Stuffing Quantity (20/40/40H)	70/147/168 (Unit)
Operation Temperature Range	16~32 (°C)
Application Area	50~75 (m2)