

Cassette 8 way indoor unit



Series	Cassette 8 way indoor unit
Model Indoor	WSTBVS-J056-MT1FUN
QCC Registration	QCC Registration
Model Panel	WZN09N
Capacity	1.6 TON / 5.6 KWH
Region	UAE

Features

 5-fold Exchanger

 Round-way Air Supply

 Long Distance Air Supply

Cassette 8 way indoor unit

Power Supply	220~240,50(60),1 (V~,Hz,Ph)
Cooling Capacity	5,6 (kW)
Heating Capacity	6,3 (kW)

Indoor Fan Motor

Model	XD30D-ZL
Brand	Panasonic
Output Power	30 (W)
Capacitor	/ (uF)
Speed	890/840/750/690 (r/min)

Indoor Coil

Number Of Row	2
Tube Pitch(a)x Row Pitch(b)	20.5×12.7 (mm)
Fin Pitch	1,4 (mm)
Fin Material	Hydrophilic aluminum fin
Tube Outside Dia.And Material	φ7， Inner grooved (mm)
Coil Length x Height x Width	1305×205×25.4 (mm)
Heat Exchanging Area	8,64 (m2)

Operation Temperature Range	16~32 (°C)
Application Area	25~45 (m2)

Stuffing Quantity (20/40/40H)	216/432/486 (Unit)
-------------------------------	--------------------

Air Flow Volume (H/M/L Speed)	
500/375/250 (CFM)	850/638/425 (m3/h)

Indoor Unit

Indoor Air Flow (Tu/Hi/Mi/Lo)	800/760/680/620 (m3/h)
Noise Level(Tu/Hi/Mi/Lo)	45/43/40/38 (dB/A)
Net Dimension (W×D×H)	570×570×260 (mm)
Packing Dimension (W×D×H)	720×650×290 (mm)
Net Weight	15,5 (kg)
Gross Weight	18,5 (kg)

Panel

Net Dimension (W×D×H)	650x650x55 (mm)
Packing Dimension (W×D×H)	710x710x80 (mm)
Net Weight	2,2 (kg)
Gross Weight	3,7 (kg)

Refrigerant Pipe

Liquid Side	6,35 (mm)
Gas Side	12,7 (mm)
Drainage	R3/4in(DN20) (mm)

Wiring specification

Power Wiring (Indoor)	3×1.5 (mm)
A B Signal Wiring(IDU&ODU, IDU&IDU)	2×0.5 (mm)