

Package Unit



Features

ESMA certificate

 Compatibility with 3rd party thermostats

 XYE Centralized Control port

 Multiple Protection Design

Package Unit

Power Supply	Max. input consumption	Sound Pressure Level	72 (dB)
380-415V 3N~ 50Hz	24.1 (kW)	Drive type	Direct
Capacity		Net Dimension (WxDxH)	2220x1260x2230 (mm)
Cooling (T3)	Cooling (T3)	Packing Dimension (WxDxH)	2240x1280x2250 (mm)
173000 (Btu/h)	50.7 (kw)	Net Weight	580 (Kg)
Electric Data		Gross Weight	590 (Kg)
Rated Cooling Power Input (T3)	Max Current (T3)	Indoor Fan	
15.60 (kW)	47 (A)	Type / Quantity	Centrifugal / 1
Performance		Refrigerant Pipe	
EER 1 (T3)	EER 2 (T3) (International)	Type	R410A
11.10 (Btu/h)	8.40 (Btu/h)	Refrigerant volume	11.2 (kg)
Indoor Fan Air Flow	5700 (CFM)	Refrigerant Control	Thermostatic expansion valve
Outdoor Fan		Ambient temperature	15°C-55°C
Type / Quantity	Motor type	External Static Pressure (Standard)	Default:110;0-300 (Pa)
Axial / 2	AC		